

TERMINATOR ADVANTAGE™

Model 1260 Multi-Zone 2-Way Audio



FULLY INTEGRATED, QUICK-CONNECT TWO-WAY AUDIO VERIFICATION MODULE WITH 8 MICROPHONE, SPEAKER AND RELAY ZONES EXPANDABLE TO 48 ZONES!

The EAGLE Model 1260, a.k.a. FALSE ALARM TERMINATOR ADVANTAGE™, provides up to **48 individual zones of microphones, speakers and relays**. A system capable of approx. 200 microphones and speakers! More zones (mic's, speakers & relays, too) than any other add-on two way voice system available. Each zone is individually or zone follower addressable for maximum flexibility and performance. It is the dealer's choice for commercial installations.

The microprocessor controlled two-way audio technology provides central station detection with Eagle's exclusive auto-disconnect feature, extensive central station control features and auto call back capability. Central station personnel can also invoke high-gain talk and high-gain listen capabilities on demand. Automatic warning tones, built-in adjustable speaker amplifier and ten Amp DPDT disconnect relay are all standard. The EAGLE TERMINATOR ADVANTAGE™ features modular design for maximum flexibility. **The new power microphone with EMT™ requires only two (2) standard wires; no shielding required¹!** User defined access codes provide maximum security for call-backs.

SYSTEM COMPATIBILITY

The EAGLE TERMINATOR ADVANTAGE™ allows you to provide two-way audio verification with any 12V control panel. Additional speakers and microphones can be added to the system via standard cabling. Dual edge trip triggering and auto-trigger make it ideal for a fast, easy installation.

ORDERING INFORMATION

P/N 301260 Terminator Advantage
P/N 301260C Terminator Advantage Kit (Includes 301260,
301262-2 Power Supply and 115031 Xfmr)
P/N 301261 8 Zone Expansion Module

OPTIONAL MODULES & PRODUCTS

EAGLE 1261 Eight Zone Expansion Module
EAGLE 1262-2 2.5A Supervised Audio Power Supply
EAGLE 115031 16.5VAC 40VA Transformer
EAGLE 1450 Digitally Stored Audio Module
EAGLE 1403 Remote Controlled Relay Module
EAGLE 2172F Flush Mount Speaker/Microphone
EAGLE 2172S Surface Mount Speaker/Microphone
EAGLE 2102P Microphone w/ Mounting Plate
EAGLE 2150 Speaker (Surface or Flush available)
EAGLE 119813 Large Steel Can for 1260/1261/1262



FEATURES

- ◆ **EIGHT individual microphone, speaker & relay zones expandable to 48 zones**
- ◆ **Selectable NC or NO relay outputs**
- ◆ **LED indicators for relays zones**
- ◆ **Voice prompted programming & annunciation**
- ◆ **Voice response to system interrogation**
- ◆ **Two wire power microphones with EMT™**
- ◆ **Optional Digitally Stored Audio Module**
- ◆ Microprocessor Control with Quick Programming
- ◆ Auto-Trip Function
- ◆ Watchdog circuit
- ◆ **LED status indicator**
- ◆ **EEPROM for maximum flexibility**
- ◆ **User defined access codes**
- ◆ Integrated Siren Driver
- ◆ Dual Trigger Circuit (positive & negative edges)
- ◆ **Two Dual Trip Circuit (Enable Input)**
- ◆ Built In Auto Answering w/ Ans. Machine Bypass
- ◆ Central Station Sensing/Auto Disconnect
- ◆ Dual Form C (DPDT) Siren Disconnect Relays
- ◆ Last Minute & Last 30 Seconds Warning Tones
- ◆ Beep/Warning Disable Function
- ◆ **Individually (zone) Adjustable Mic Gain**
- ◆ **Local & Remote Telephone Access**
- ◆ Over Current Protection (auto-reset polyfuse)

SPECIFICATIONS

1260 Dimensions: 10.00"W x 8.00"L" x 1.75"H
1261 Dimensions: 10.00"W x 4.75"L" x 1.75"H
Power: Voltage (1260): 12 VDC ± 2 VDC
Current (Standby): 10 mA; Trip: Max. 0.5 mA

All specifications preliminary & subject to change w/o notice.
Note 1: On wire runs less than 100 feet.

77 Dingens Street, Suite B, Buffalo, NY 14206-2307

Tel: 716.827.6500 Fax: 716.827.6505

SALES INFORMATION: 1-800-334-7188
email: sales@eagle-security.com

© 1998-2006 Eagle Security Products, Inc.

TECHNICAL SUPPORT: 1-800-447-E3 A2 G4 L5 E
http://www.eagle-security.com

Rev 5.1