

# MODEL 1262 Audio Grade Supervised Power Supply



**AUDIO QUALITY SUPERVISED POWER SUPPLY IS AVAILABLE IN TWO CONFIGURATIONS - 1.5 AMP OR 2.5 AMP WITH SPDT RELAY OUTPUT.**

The EAGLE Model 1262 Supervised Audio Power Supply offers 12 VDC output at either 1.5 Amps (1262-1) or 2.5 Amps (1262-2). The units have been designed to supply clean output ideal for audio applications and any application where a high quality supply is critical.

The units feature an auto resetting polyfuse design in place of traditional one time fuse. This allows the power supplies to recover from one time surges without permanent power failure. Also featured are battery charging circuit and one Amp supervisory relay output. Status LED's include AC ON, DC ON, BATTERY REVERSAL and LOW BATTERY.

## SYSTEM COMPATIBILITY

The Model 1262 is the ideal power supply for all of your 12 VDC needs! Available in two configurations, 1.5 Amp and 2.5 Amp, it is capable of solving most of your system requirements.

## ORDERING INFORMATION

P/N 301262-1 1.5A Supervised Audio Power Supply  
P/N 301262-2 2.5A Supervised Audio Power Supply

## OPTIONAL ACCESSORIES

P/N 115031 16.5V 40VA Transformer w/ GROUND  
P/N 119813 12" x 14.5" x 3" Steel Power Supply Can w/lock  
P/N 119814 11" x 11" x 3" Steel Power Supply Can w/lock



## FEATURES

- ◆ Regulated 13.8 VDC continuous output at 2.5 Amps (1262-2)
- ◆ Regulated 13.8 VDC continuous output at 1.5 Amps (1262-1)
- ◆ Built-in battery charging circuit
- ◆ *Auto resetting polyfuse design*
- ◆ *Battery reversal protection and status LED*
- ◆ *Low battery supervision, output & status LED*
- ◆ Form C supervision relay
- ◆ *AC and DC status LED's*
- ◆ *ON / OFF Power switch*
- ◆ MOV lightning/transient protection
- ◆ Precision Voltage Regulator
- ◆ External 12 VDC input connection
- ◆ Convenient 45 degree terminal strip
- ◆ Optional UL listed Class II plug-in transformer

## SPECIFICATIONS

Dimensions: 5.75"W x 3.25L" x 1.75"H  
Voltage output: 12 VDC  $\pm$  0.1 VDC  
Current Output 301262-1: 1.5 Amps DC  
Current Output 301262-2: 2.5 Amps DC  
Supervisory Relay contacts: 1 Amp @ 250 VDC

All specifications preliminary & subject to change w/o notice.

77 Dingens Street, Suite B, Buffalo, NY 14206-2307

Tel: 716.827.6500 Fax: 716.827.6505

SALES INFORMATION: 800.334.7188  
email: sales@eagle-security.com  
© 2006 Eagle Security Products, Inc.

TECHNICAL SUPPORT: 800.447.E3A2G4L5E  
http://www.eagle-security.com  
Rev. 2.2 5/06