
EAGLE 1408

REMOTE ARM/DISARM MODULE



Remote and local arming and disarming of control panels.

The Eagle Model 1408 REMOTE ARM / DISARM MODULE with VOICE is an OEM version of Eagle's very successful Model 1407. The module allows the remote arming and disarming of any alarm system which has a mechanical key input. Additionally, the 1408 offers buss interfacing for maximum voice response system information. The 1408 can be called from any outside phone and will answer the call in a pre-programmed number of rings dependent upon the control panel armed status (toll saver too!). Additionally, it can be accessed from any local phone!

The module allows a four digit access code which is programmable. Programming is accomplished via a standard touch tone phone and the telco network. All options and access codes are stored in non-volatile, removable EEPROM.

The Model 1408 utilizes the latest in digitally stored voice messages for confirmation and system status. Two versions are available, English voice and Spanish voice.

SYSTEM COMPATIBILITY

The EAGLE 1408 provides a full range of computability for use with any alarm panel with a manual key input. Further system enhancement is obtained through the armed status input which utilizes a system armed output from the control panel.

ACCESSORIES

EAGLE 1403 Remote Control Relay Module

OPTIONS:

Optional local access during alarm reporting is available at additional cost. Contact Eagle for further information.

**OEM
VERSION!**

FEATURES

- ◆ Voice confirmation in English
- ◆ Buss interfacing
- ◆ Local phone access
- ◆ Auto-answer circuit with answering machine and download bypass
- ◆ Single C output (SPDT)
- ◆ Up to 8 additional relays using EAGLE 1403
- ◆ Non-volatile, removable EEPROM
- ◆ Programming via Tone phone
- ◆ Two levels of access (master/slave)
- ◆ Four digit code programmability

REMOTE CONTROL FEATURES

- ◆ Arm and Disarm
- ◆ Change codes
- ◆ Change slave status
- ◆ System status

WARRANTY

All Eagle Security Products, Inc. Products are backed by our standard "out-of-the-box" failure warranty: If it's bad, we'll replace it. Contact Eagle for details.

SPECIFICATIONS

Dimensions: 4.00" x 4.00"

Power: Voltage: 12 VDC \pm 2 VDC

Current (Standby/Active Remote/Active Local):
22mA/50mA/154mA

All specifications subject to change without notice.

HOW TO ORDER

Contact Eagle directly for OEM sales.

77 Dingens Street, Suite B, Buffalo, NY 14206-2307

Tel: 716.827.6500 Fax: 716.827.6505

SALES INFORMATION: 800.334.7188
email: sales@eagle-security.com

© 1998-2006 Eagle Security Products, Inc.

TECHNICAL SUPPORT: 800.447.E3A2G4L5E
<http://www.eagle-security.com>

Rev. 1.3 05/2006