

TERMINATOR ADVANTAGE™

Multi-Zone 2-Way Audio



FULLY INTEGRATED, QUICK-CONNECT TWO-WAY AUDIO VERIFICATION MODULE WITH 8 MICROPHONE, SPEAKER AND RELAY ZONES EXPANDABLE TO 48 ZONES!

The EAGLE FALSE ALARM TERMINATOR ADVANTAGE™ provides up to **48 individual zones of microphones, speakers and relays**. A system capable of approx. 200 microphones and speakers! More zones (mic's, speakers & relays, too) than any other add-on two way voice system available. Each zone is individually or zone follower addressable for maximum flexibility and performance. It is the dealer's choice for commercial installations.

The microprocessor controlled two-way audio technology provides central station detection with Eagle's exclusive auto-disconnect feature, extensive central station control features and auto call back capability. Central station personnel can also invoke high-gain talk and high-gain listen capabilities on demand. Automatic warning tones, built-in adjustable speaker amplifier and ten Amp DPDT disconnect relay are all standard. The EAGLE TERMINATOR ADVANTAGE™ features modular design for maximum flexibility. **The new power microphone with EMT™ requires only two (2) standard wires; no shielding required¹!** User defined access codes provide maximum security for call-backs.

SYSTEM COMPATIBILITY

The EAGLE TERMINATOR ADVANTAGE™ allows you to provide two-way audio verification with any 12V control panel. Additional speakers and microphones can be added to the system via standard cabling. Dual edge trip triggering and auto-trigger make it ideal for a fast, easy installation.

OPTIONAL MODULES

EAGLE 1261 Eight Zone Expansion Module
EAGLE 1262 2.5A Supervised Audio Power Supply
EAGLE 1450 Digitally Stored Audio Module
EAGLE 1403 Remote Controlled Relay Module
EAGLE 2172F Flush Mount Speaker/Microphone
EAGLE 2172S Surface Mount Speaker/Microphone
EAGLE 2102P Microphone w/ Mounting Plate
EAGLE 2150 Speaker (Surface or Flush available)
EAGLE 119813 Large Steel Can for 1260/1261/1262

TERMINATOR
48 ZONES!
ADVANTAGE

FEATURES

- ◆ **EIGHT individual microphone, speaker & relay zones expandable to 48 zones**
- ◆ **Selectable NC or NO relay outputs**
- ◆ **LED indicators for relays zones**
- ◆ **Voice prompted programming & annunciation**
- ◆ **Voice response to system interrogation**
- ◆ **Two wire power microphones with EMT™**
- ◆ **Optional Digitally Stored Audio Module**
- ◆ Microprocessor Control with Quick Programming
- ◆ Auto-Trip Function
- ◆ Watchdog circuit
- ◆ **LED status indicator**
- ◆ **EEPROM for maximum flexibility**
- ◆ **User defined access codes**
- ◆ Integrated Siren Driver
- ◆ Dual Trigger Circuit (positive & negative edges)
- ◆ **Two Dual Trip Circuit (Enable Input)**
- ◆ Built In Auto Answering w/ Ans. Machine Bypass
- ◆ Central Station Sensing/Auto Disconnect
- ◆ Dual Form C (DPDT) Siren Disconnect Relays
- ◆ Last Minute & Last 30 Seconds Warning Tones
- ◆ Beep/Warning Disable Function
- ◆ **Individually (zone) Adjustable Mic Gain**
- ◆ **Local & Remote Telephone Access**
- ◆ Extend and Hang-up Features
- ◆ Over Current Protection (auto-reset polyfuse)

SPECIFICATIONS

1260 Dimensions: 10.00"W x 8.00L" x 1.75"H
1261 Dimensions: 10.00"W x 4.75L" x 1.75"H
1262 Dimensions: 5.75"W x 3.25L" x 1.75"H
Power: Voltage (1260): 12 VDC ± 2 VDC
Current (Standby): 10 mA
Trip Current: Maximum: 0.5 mA (500 uA)

All specifications preliminary & subject to change w/o notice.
Note 1: On wire runs less than 100 feet.

11650 Genesee St. Suite #2, Alden, NY 14004-9630
Tel: 716.937.0095 Fax: 716.937.3127

SALES INFORMATION: 1-800-334-7188
email: sales@eagle-security.com
© 1998 Eagle Security Products, Inc.

TECHNICAL SUPPORT: 1-800-447-E₃A₂G₄L₅E
<http://www.eagle-security.com>
Rev 4.4